



In-Ground, Step and Deck Lighting



SC-B101B – Round Floor Light

0.5W DC12V LED SMD3350 7 lumen 2800 –
 3000K Warm White
 Beam Angle 120°
 Lifespan 50,000h
 IP67
 304/316 Stainless Steel
 High intensity tempered glass
 1m cable with male connector
 Plug and play waterproof connections
 Ultra-thin design 9mm
 Size ø 58mm
 Hole size ø 50mm
 3 year limited warranty



SC-B102B – Square Floor Light

0.6W DC12V LED SMD3350 9 lumen 2800 –
 3000K Warm White
 Beam Angle 120°
 Lifespan 50,000h
 IP67
 304/316 Stainless Steel
 High intensity tempered glass
 1m cable with male connector
 Plug and play waterproof connections
 Ultra-thin design 9mm
 Size 58 x 58mm
 Hole size 50 x 50mm
 3 year limited warranty



SC-B106A – Step or Deck Light

0.4W DC12V LED SMD5050 10 lumen 2800 –
 3000K Warm White
 Beam Angle 90°
 Lifespan 50,000h
 IP65
 Zinc alloy
 1m cable with male connector
 Plug and play waterproof connections
 Size ø 35mm
 Hole size ø 24mm
 3 year limited warranty



SC-B106A-S – Stainless Steel Step or Deck Light

0,08W DC12V LED SMD2835 10 lumen 2800 –
 3000K Warm White
 Beam Angle 90°
 Lifespan 50,000h
 IP65
 316 Stainless Steel
 2 x 1m cable, one with male connector, one
 with female connector
 Plug and play waterproof connections
 Size ø 35mm
 Hole size ø 24mm
 3 year limited warranty



SC-B107A – 80mm Round Deck Light

2.5W DC12V LED SMD2835 170 lumen 2800 –
 3000K Warm White
 Beam Angle 120°
 Lifespan 50,000h
 IP67
 304/316 Stainless Steel
 High intensity tempered glass
 2 x 0,5m cable, one with male connector, one
 with female connector
 Plug and play waterproof connections
 Size ø 80mm
 Height 26mm
 Hole size ø 60mm
 3 year limited warranty



SC-B108A – 60mm Round Deck Light

1.5W DC12V LED SMD2835 110 lumen 2800 –
 3000K Warm White
 Beam Angle 120°
 Lifespan 50,000h
 IP67
 304/316 Stainless Steel
 High intensity tempered glass
 2 x 0,5m cable, one with male connector, one
 with female connector
 Plug and play waterproof connections
 Size ø 60mm
 Height 26mm
 Hole size ø 40mm
 3 year limited warranty



SC-B109A – 45mm Round Deck Light

1W DC12V LED SMD2835 75 lumen 2800 –
 3000K Warm White
 Beam Angle 120°
 Lifespan 50,000h
 IP67
 304/316 Stainless Steel
 High intensity tempered glass
 2 x 0,5m cable, one with male connector, one
 with female connector
 Plug and play waterproof connections
 Size ø 45mm
 Height 26mm
 Hole size ø 30,5mm
 3 year limited warranty



SC-B110A – 30mm Round Deck Light

0,6W DC12V LED SMD2835 40 lumen 2800 –
 3000K Warm White
 Beam Angle 120°
 Lifespan 50,000h
 IP67
 304/316 Stainless Steel
 High intensity tempered glass
 2 x 0,5m cable, one with male connector, one
 with female connector
 Plug and play waterproof connections
 Size ø 30mm
 Height 26mm
 Hole size ø 20mm
 3 year limited warranty



In-Ground, Step and Deck Lighting



SC-B111 – 18mm Round Deck Light

0,4W DC12V LED SMD2835 7 lumen 2800 –
 3000K Warm White
 Beam Angle 120°
 Lifespan 50,000h
 IP67
 304/316 Stainless Steel
 High intensity tempered glass
 2 x 0,5m cable, one with male connector, one with female connector
 Plug and play waterproof connections
 Size ø 18mm
 Height 26mm
 Hole size ø 12mm
 3 year limited warranty



SC-F101A – 26mm Half-Moon Deck or Step Light

0,6W DC12V LED SMD2835 8 lumen 2800 –
 3000K Warm White
 Beam Angle 90°
 Lifespan 50,000h
 IP65
 Aluminium
 1m cable, one with male connector
 Plug and play waterproof connections
 Size ø 26mm
 Height 41mm
 Hole size ø 18mm
 3 year limited warranty



SC-F103A – 28mm Deck Light or Step Light

0,8W DC12V LED SMD2835 12 lumen 2800 –
 3000K Warm White
 Beam Angle 90°
 Lifespan 50,000h
 IP67
 316 Stainless Steel
 2 x 1m cable, one with male connector, one with female connector
 Plug and play waterproof connections
 Size ø 28mm
 Height 28mm
 Hole size ø 22mm
 3 year limited warranty



SC-F103A-1 – 34mm Deck Light or Step Light

0,8W DC12V LED SMD2835 12 lumen 2800 –
 3000K Warm White
 Beam Angle 90°
 Lifespan 50,000h
 IP67
 304 Stainless Steel
 2 x 1m cable, one with male connector, one with female connector
 Plug and play waterproof connections
 Size ø 34mm
 Height 28mm
 Hole size ø 26mm
 3 year limited warranty



SC-F104A – 60mm In-Ground Light

0,5W DC12V LED SMD3350 7 lumen 2800 –
 3000K Warm White
 Beam Angle 120°
 Lifespan 50,000h
 IP67
 304/316 Stainless Steel
 1m cable, one with male connector
 Plug and play waterproof connections
 Size ø 60mm
 Height 29,5mm
 Hole size ø 55mm
 3 year limited warranty



SC-F108A – 20mm In-Ground or Deck Light

0,6W DC12V LED SMD2835 7 lumen 2800 –
 3000K Warm White
 Beam Angle 120°
 Lifespan 50,000h
 IP67
 316 Stainless Steel
 2 x 1m cable, one with male connector, one with female connector
 Plug and play waterproof connections
 Size ø 20mm
 Height 22,5mm
 Hole size ø 18mm
 3 year limited warranty



SC-F109A-1 – 58,5mm In-Ground Light

0,75W DC12V LED SMD3535 3 lumen 2800 –
 3000K Warm White
 Single light source
 Beam Angle 40°
 Lifespan 50,000h
 IP67
 Black powder-coated Aluminium
 2 x 1m cable, one with male connector, one with female connector
 Plug and play waterproof connections
 Plastic sleeve supplied
 Size ø 58,5mm
 Height 92mm
 Hole size ø 42mm
 3 year limited warranty



SC-F109A-2 – 58,5mm In-Ground Light

0,75W DC12V LED SMD3535 3 lumen 2800 –
 3000K Warm White
 Double light source
 Beam Angle 40° per light source
 Lifespan 50,000h
 IP67
 Black powder-coated Aluminium
 2 x 1m cable, one with male connector, one with female connector
 Plug and play waterproof connections
 Plastic sleeve supplied
 Size ø 58,5mm
 Height 92mm
 Hole size ø 42mm
 3 year limited warranty




In-Ground, Step and Deck Lighting



SC-F110A – 50mm In-Ground Light

0,85W DC12V LED SMD3528 40 lumen 2800 – 3000K Warm White
Beam Angle 120°
Lifespan 50,000h
IP67
Black powder-coated Aluminium
2 x 1m cable, one with male connector, one with female connector
Plug and play waterproof connections
Plastic sleeve supplied
Size ø 50mm
Height 80mm
Hole size ø 42mm
3 year limited warranty



SC-J103A – Garden Light

AC85-264V 8W LED COB 520 lumen 2800 – 3000K Warm White
Beam Angle 60°
Lifespan 50,000h
IP67
Black powder-coated Aluminium
Size ø 50mm x 80mm
Height 210mm
3 year limited warranty



SC-Y1203B - 3W LED Driver

DC12V
Input 90-260VAC 50/60Hz
IP67
Size 53 x 35 x 23mm



SC-Y1208B - 8W LED Driver

DC12V
Input 90-260VAC 50/60Hz
IP67
Size 71 x 46 x 27mm



SC-Z103B - Extension Cable

2m 2 pin cable with waterproof connections



SC-1230B - 30W LED Driver

DC12V
Input 90-260VAC 50/60Hz
IP67
Size 196 x 52 x 30mm



SC-Z106A - Junction Box

2 pin waterproof junction box